

PANEL SCREWS W/
WASHERS @ 24" O.C.
W/ MINIMUM 1"
PENETRATION INTO TOP
PLATE MATERIAL (U.N.O.)

SQUARE-CUT EAVE
(SEE DETAIL EP-414)

BEVELED TOP
PLATE (SEE
DETAIL EP-402)

PANEL SCREWS W/
WASHERS @ 24" O.C.
W/ MINIMUM 1"
PENETRATION INTO
TIMBER FRAME (U.N.O.)

$\frac{5}{8}$ " SPACER BETWEEN
PANELS AND TIMBER
FRAME MEMBER WHEN
 $\frac{1}{2}$ " GYPSUM BOARD ON
PANELS (USE $\frac{3}{4}$ "
SPACER WHEN $\frac{5}{8}$ "
GYPSUM BOARD ON
PANELS)

TIMBER FRAME
MEMBER

GYPSUM BOARD PER
CODE REQUIREMENTS

SECTION
NOT TO SCALE

* DETAIL COURTESY OF PREMIER BUILDING SYSTEMS

DETAIL TITLE : TIMBER FRAME MEMBER CONNECTION

DETAIL NO. : EP-118

PAGE NO. : 1 - 18

UPDATED : 2/5/2009

Extreme Panel
Technologies, Inc.
QUALITY EFFICIENT BUILDING SYSTEMS